

DALA-GRIPEN

DG är stark och lätt timmergrip med bra inrullnings egenskaper och hög fyllnadsgrad, passar på allt tex. Skogsvagnar, skotare och lastbilar.



DG8



DG12



DG14 / DG20



DG28-35



DG29-36



DG42

MODEL			DG8	DG12	DG14	DG20-1	DG20-2	DG22	DG25	DG28	DG29	DG35	DG36	DG42	DG55
A	HEIGHT WHEN OPEN	mm	405	503	495	605	550	520	615	735	695	760	735	845	945
B	MAX OPENING	mm	865	1080	1000	1205	1250	1300	1400	1435	1560	1820	1730	2000	2250
C	HEIGHT WHEN CLOSED	mm	325	355	350	405	415	420	475	520	550	600	570	620	730
D	MIN GRIPING DIAMETER	mm	60	50	57	50	73	70	90	105	110	125	120	125	125
E	LENGTH WHEN CLOSED	mm	450	615	545	700	645	660	730	810	830	930	890	1045	1150
F	GRIPPING AREA	m ²	0,08	0,12	0,14	0,2	0,2	0,22	0,25	0,28	0,29	0,35	0,36	0,42	0,55
G	WIDTH	mm	220	200	260	310	280	364	375	420	420	485	472	490	600
H	MAX WIDTH	mm	220	270	260	400	295	364	390	430	488	495	540	500	620
WEIGHT		kg	25	46	45	77	68	88	125	170	240	250	280	290	500
MAX LOAD		kg	350	550	1200	1000	2000	2500	3500	3500	3500	5000	5000	5000	5000
MAX WORKING PRESSURE		Bar	180	200	200	250	250	250	250	250	250	250	250	250	250
CYLINDER FORCE		kN	35,3	35,3	35,3	72	71,6	71,6	115,5	115,5	146,2	146,2	180,5	180,5	196
GRIPPING FORCE ARMS TIP		kN	6,3	8,9	7	15	12,1	9	19,3	19,2	17,1	25,4	17,1	32,8	35
OPENING TIME 70L/MIN		s	0,14	0,19	0,16	0,44	0,28	0,4	0,62	0,5	0,9	0,8	1	1,3	1,5
CLOSING TIME 70L/MIN		s	0,2	0,3	0,24	0,66	0,46	0,6	0,83	0,9	1,5	1,3	1,6	1,8	2
ROTATOR DIRECT CONNECTION *			F	B	A	D	A	B	D	D	C	C	C	C	H
ORDER CODE			DG8	DG12	DG14	DG20-1	DG20-2	DG22	DG25	DG28	DG29	DG35	DG36	DG42	DG55

* Please, see the rotator connection page for detailed information.