

Einböck

When hoeing
is joy!

DATA SHEET HOEING TECHNOLOGY



WWW.EINBOECK.EU

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Top link steering	Camera steering system ROW-GUARD	Row button for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including lane indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
						Possible	Standard												
CHOPSTAR 1-30 up to 1 tine up to 30 cm row spacing	12-rows	320	320	700	II/28	20-30	25	40/30	✓	●	-	●	●	●	✓	-	-	-	-
	16-rows	300	420	1200	II/28	20-30	25	70/51	✓	●	-	●	●	●	-	✓	-	-	-
	24-rows	300	620	1560	II/28	20-30	25	80/59	✓	●	-	●	●	●	-	✓	-	-	-
	32-rows	330	820	2120	II/28	20-30	25	90/66	-	●	-	-	-	●	-	✓	-	-	-
	X-rows	C	C	C	C	20-30	C	C	C	C	-	C	C	C	C	C	C	C	C
CHOPSTAR 3-60 up to 3 tines up to 60 cm row spacing	3-rows	160	160	385	II/28	≤ 60	45	30/22	✓	●	●	●	●	●	✓	-	-	-	-
	4-rows	200	200	450	II/28	≤ 60	45	30/22	✓	●	●	●	●	●	✓	-	-	-	-
	5-rows	245	245	515	II/28	≤ 60	45	30/22	✓	●	●	●	●	●	✓	-	-	-	-
	6-rows	300	300	580	II/28	≤ 60	45	40/30	✓	●	●	●	●	●	✓	-	-	-	-
	7-rows	300	335	780	II/28	≤ 60	45	50/37	✓	●	●	●	●	●	✓	-	-	-	-
	8-rows	300	380	880	II/28	≤ 60	45	60/44	✓	●	●	●	●	●	-	✓	-	-	-
	12-rows	300	560	1210	II/28	≤ 60	45	70/51	✓	●	●	●	●	●	-	✓	-	-	-
	15-rows	320	695	1570	II/28	≤ 60	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18-rows	480	830	1870	III/36	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		300	830	2060	II/28	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	✓	-	-
	24-rows	670	1100	2360	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1100	2570	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	≤ 60	C	C	C	C	C	C	C	C	C	C	C	C	C
CHOPSTAR 5-90 up to 5 tines up to 90 cm row spacing	2-rows	160	160	430	II/28	≤ 90	70	20/15	✓	●	●	●	●	●	✓	-	-	-	-
	4-rows	300	300	560	II/28	≤ 90	70	40/30	✓	●	●	●	●	●	✓	-	-	-	-
		300	300	840	II/28	≤ 90	70	50/37	✓	●	●	●	●	●	-	✓	-	-	-
	6-rows	440	440	820	II/28	≤ 90	70	60/44	✓	●	●	●	●	●	✓	-	-	-	-
		300	440	1010	II/28	≤ 90	70	60/44	✓	●	●	●	●	●	-	✓	-	-	-
	7-rows	300	510	1090	II/28	≤ 90	70	70/51	✓	●	●	●	●	●	-	✓	-	-	-
	8-rows	580	580	990	II/28	≤ 90	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
		320	580	1170	II/28	≤ 90	70	80/59	✓	●	●	●	●	●	-	✓	-	-	-
	12-rows	480	860	1810	III/36	≤ 90	70	140/103	-	●	●	-	-	-	-	✓	-	✓	●
		300	860	2040	II/28	≤ 90	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	16-rows	690	1140	2250	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1140	2500	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	≤ 90	C	C	C	C	C	C	C	C	C	C	C	C	C
CHOPSTAR 10-150 up to 10 tines up to 150 cm row spacing	2-rows	300	255	480	II/28	≤ 150	150	40/30	✓	●	●	●	●	●	✓	-	-	-	-
	3-rows	300	405	1000	II/28	≤ 150	150	60/44	✓	●	●	●	●	●	-	✓	-	-	-
	X-rows	C	C	C	C	19-30	C	C	C	C	C	C	C	C	C	C	C	C	C

Conversion cm in inch = cm / 2,54 Conversion cm in feet = cm / 30,48

✓ = standard equipment

● = optionally available

V = version (selection)

K = customer adaption or request

- = not possible

	PROTECTIVE ELEMENTS					WORKING TOOLS													ACCESSORIES				
	Discs		Rotary hoe crop-protection-star	Sheets	Without	Tines	Elements	Cutting plate	Angle knives	Cutting discs	Hoeing stars	Heaping sweeps	Heaping elements	Heaping discs	Weeder tines behind the element	Guided hill weeder	Finger hoe	Rotation weeder element	Section Control Hydr. folding system	Seeder P-BOX-STI JUMBO-SEED	Warning signs + LED lights to the rear	Warning signs + LED lights to the front and rear	Warning signs for front units with indicator to the front
	●	-	-	●	✓	13	13	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	●	-	-	●	✓	17	17	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	●	-	-	●	✓	25	25	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	●	-	-	●	✓	33	33	-	-	-	-	●	-	-	●	-	-	-	●	●	●	●	●
	C	-	-	C	C	C	C	-	-	-	-	C	-	-	C	-	-	-	C	C	C	C	C
	●	●	-	●	✓	10	4	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	13	5	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	16	6	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	19	7	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	22	8	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	25	9	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	37	13	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	●
	●	●	-	●	✓	46	16	-	●	-	-	●	-	●	●	-	●	●	●	●	●	-	-
	●	●	-	●	✓	55	19	-	●	-	-	●	-	●	●	-	●	●	●	●	●	-	-
	●	●	-	●	✓	55	19	-	●	-	-	●	-	●	●	-	●	●	●	●	●	-	-
	●	●	-	●	✓	73	25	-	●	-	-	●	-	●	●	-	●	●	●	●	●	-	-
	●	●	-	●	✓	73	25	-	●	-	-	●	-	●	●	-	●	●	●	●	●	-	-
	C	C	-	C	C	C	C	-	C	-	-	C	-	C	C	-	C	C	C	C	C	C	C
	-	●	●	●	✓	11	3	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	21	5	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	21	5	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	31	7	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	31	7	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	36	8	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	41	9	-	●	-	-	●	●	●	●	-	●	●	●	●	●	-	-
	-	●	●	●	✓	41	9	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	●	●	✓	61	13	-	●	-	-	●	●	●	●	-	●	●	●	●	●	-	-
	-	●	●	●	✓	61	13	-	●	-	-	●	●	●	●	-	●	●	●	●	●	-	-
	-	●	●	●	✓	81	17	-	●	-	-	●	●	●	●	-	●	●	●	●	●	-	-
	-	●	●	●	✓	81	17	-	●	-	-	●	●	●	●	-	●	●	●	●	●	-	-
	-	C	C	C	C	C	C	-	C	-	-	C	C	C	C	-	C	C	C	C	C	C	C
	-	●	-	●	✓	20	4	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	●	-	●	✓	30	6	-	●	-	-	●	●	●	●	-	●	●	●	●	●	●	●
	-	C	-	C	C	C	C	-	C	-	-	C	C	C	C	-	C	C	C	C	C	C	C

Please clarify directly with an Einböck consultant whether additional options can be combined with each other or whether special parts may be required for options to be implemented (e.g. deviation from row spacing).

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Top link steering	Camera steering system ROW-GUARD	Row button for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including lane indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
						Possible	Standard												
CHOPSTAR-TWIN up to 4 tines 2 cutting discs 35-75 cm row spacing	5-rows	230	200	580	II/28	35-75	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	6-rows	275	245	610	II/28	35-75	45	40/30	✓	●	●	●	●	-	✓	-	-	-	-
	8-rows	300	335	940	II/28	35-75	45	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	12-rows	300	515	1330	II/28	35-75	45	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	15-rows	320	650	1730	II/28	35-75	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18-rows	480	785	2070	III/36	35-75	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		305	785	2260	II/28	35-75	45	130/96	-	●	●	-	-	-	-	-	✓	-	-
	24-rows	670	1055	2650	III/36	35-75	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1055	2860	III/36	35-75	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	II/28	35-75	C	C	C	C	C	C	C	-	C	C	C	C	C
CHOPSTAR-VERSO 3-60 up to 3 tines 2 cutting discs 45-60 cm row spacing	3-rows	160	160	425	II/28	45-60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	200	200	500	II/28	45-60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	5-rows	245	245	575	II/28	45-60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	6-rows	300	300	650	II/28	45-60	45	40/30	✓	●	●	●	●	-	✓	-	-	-	-
	7-rows	300	335	905	II/28	45-60	45	50/30	✓	●	●	●	●	-	-	✓	-	-	-
	8-rows	300	380	980	II/28	45-60	45	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	12-rows	300	560	1360	II/28	45-60	45	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	15-rows	320	695	1750	II/28	45-60	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18-rows	480	830	2090	III/36	45-60	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		300	830	2280	II/28	45-60	45	130/96	-	●	●	-	-	-	-	-	✓	-	-
	24-rows	670	1100	2650	III/36	45-60	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1100	2860	III/36	45-60	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	45-60	C	C	C	C	C	C	C	C	C	C	C	C	C
CHOPSTAR-VERSO 5-80 up to 5 tines 2 cutting discs 45-80 cm row spacing	2-rows	160	160	455	II/28	60-80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	300	300	610	II/28	60-80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	890	II/28	60-80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6-rows	440	440	890	II/28	60-80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1080	II/28	60-80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	7-rows	300	510	1170	II/28	60-80	70	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	8-rows	580	580	1090	II/28	60-80	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
		320	580	1270	II/28	60-80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
	12-rows	480	860	1950	III/36	60-80	70	140/103	-	●	●	-	-	-	-	✓	-	✓	●
		300	860	2180	II/28	60-80	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	16-rows	690	1140	2440	III/36	60-80	70	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1140	2690	III/36	60-80	70	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	60-80	C	C	C	C	C	C	C	C	C	C	C	C	C

Conversion cm in inch = cm / 2,54 Conversion cm in feet = cm / 30,48

✓ = standard equipment

● = optionally available

V = version (selection)

K = customer adaption or request

- = not possible

	PROTECTIVE ELEMENTS					WORKING TOOLS												ACCESSORIES					
	Discs		Rotary hoe crop-protection-star	Sheets	Without	Tines	Elements	Cutting plate	Angle knives	Cutting discs	Hoeing stars	Heaping sweeps	Heaping elements	Heaping discs	Weeder tines behind the element	Guided hill weeder	Finger hoe	Rotation weeder element	Section Control Hydr. folding system	Seeder P-BOX-STI JUMBO-SEED	Warning signs + LED lights to the rear	Warning signs + LED lights to the front and rear	Warning signs for front units with indicator to the front
	Smooth	Jagged																					
	-	-	-	-	✓	10	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	12	6	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	16	8	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	24	12	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	30	15	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	36	18	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	36	18	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	48	24	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	48	24	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	C	C	-	✓	✓	-	-	-	-	C	-	C	C	C	C	C	C	-
	-	-	-	-	✓	10	4	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	13	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	16	6	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	19	7	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	22	8	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	25	9	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	37	13	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	46	16	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	55	19	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	55	19	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	73	25	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	73	25	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	C	C	-	✓	✓	-	-	-	-	C	-	C	C	C	C	C	C	C
	-	-	-	-	✓	11	3	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	21	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	21	5	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	31	7	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	31	7	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	36	8	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	41	9	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	41	9	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	61	13	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	61	13	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	81	17	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	81	17	-	✓	✓	-	-	-	-	●	-	●	●	●	●	●	●	-
	-	-	-	-	✓	C	C	-	✓	✓	-	-	-	-	C	-	C	C	C	C	C	C	C

Please clarify directly with an Einböck consultant whether additional options can be combined with each other or whether special parts may be required for options to be implemented (e.g. deviation from row spacing).

For further options or technical information please contact our sales team. For an up-to-date overview or information, please visit our website and download the latest brochures online (www.einboeck.at/en/downloads).

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Top link steering	Camera steering system ROW-GUARD	Row button for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including lane indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
						Possible	Standard												
CHOPSTAR-PRIME 3-60 up to 3 tines 35-90 cm row spacing	3-rows	160	160	423	II/28	≤ 60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	200	200	514	II/28	≤ 60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	5-rows	245	245	591	II/28	≤ 60	45	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	6-rows	300	300	670	II/28	≤ 60	45	40/30	✓	●	●	●	●	-	✓	-	-	-	-
	7-rows	300	335	881	II/28	≤ 60	45	50/37	✓	●	●	●	●	-	✓	-	-	-	-
	8-rows	300	380	990	II/28	≤ 60	45	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	12-rows	300	560	1370	II/28	≤ 60	45	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	15-rows	320	695	1770	II/28	≤ 60	45	90/66	-	●	●	-	-	-	-	✓	-	-	-
	18-rows	480	830	2110	III/36	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		300	830	2300	II/28	≤ 60	45	130/96	-	●	●	-	-	-	-	✓	✓	-	-
	24-rows	670	1100	2670	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1100	2880	III/36	≤ 60	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	≤ 60	C	C	C	C	C	C	C	-	C	C	C	C	C
CHOPSTAR-PRIME 5-90 up to 5 tines 61-90 cm row spacing	2-rows	160	160	450	II/28	≤ 90	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	300	300	575	II/28	≤ 90	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	870	II/28	≤ 90	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6-rows	440	440	870	II/28	≤ 90	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1060	II/28	≤ 90	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	7-rows	300	510	1140	II/28	≤ 90	70	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	8-rows	580	580	1050	II/28	≤ 90	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
		320	580	1230	II/28	≤ 90	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
	12-rows	480	860	1900	III/36	≤ 90	70	140/103	-	●	●	-	-	-	-	✓	-	✓	●
		300	860	2130	II/28	≤ 90	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	16-rows	690	1140	2370	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		400	1140	2620	III/36	≤ 90	70	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	≤ 90	C	C	C	C	C	C	C	-	C	C	C	C	C

	PROTECTIVE ELEMENTS					WORKING TOOLS												ACCESSORIES					
	Discs		Rotary hoe crop-protection-star	Sheets	Without	Tines	Elements	Cutting plate	Angle knives	Cutting discs	Hoeing stars	Heaping sweeps	Heaping elements	Heaping discs	Weeder tines behind the element	Guided hill weeder	Finger hoe	Rotation weeder element	Section Control Hydr. folding system	Seeder P-BOX-ST1 JUMBO-SEED	Warning signs + LED lights to the rear	Warning signs + LED lights to the front and rear	Warning signs for front units with indicator to the front
	●	●	●	●	✓	10	4	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	13	5	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	16	6	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	19	7	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	22	8	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	25	9	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	37	13	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	46	16	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	55	19	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	55	19	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	73	25	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	73	25	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	C	C	C	C	C	C	C	-	C	-	-	C	-	C	C	-	C	C	C	C	C	C	-
	●	●	●	●	✓	11	3	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	21	5	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	21	5	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	31	7	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	31	7	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	36	8	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	41	9	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	41	9	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	61	13	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	61	13	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	81	17	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	●	●	●	●	✓	81	17	-	●	-	-	●	-	●	●	-	●	●	●	●	●	●	-
	C	C	C	C	C	C	C	-	C	-	-	-	-	C	C	-	C	C	C	C	C	C	-

ROW-CROP CULTIVATOR TYPE	DIMENSIONS AND TECHNICAL DATA								STEERING						FOLDING				
	Rows = Model	Transport width (cm)	Frame profile length S	Basic weight (approx. in kg)	Mounting category S	Row spacing (cm)		Power requirement from HP/kW	Top link steering	Camera steering system ROW-GUARD	Row button for ROW-GUARD	Hydraulic manual steering	Hydraulic steering pilot control	Front version including lane indicator for steering assistance	Rigid	Hydraulically folding	Double folding frame	Centre frame in XXL	Transport frame
						Possible	Standard												
ROLLSTAR maize version (8 stars / row) up to 80 cm row spacing	2-rows	190	160	550	II/28	> 80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	330	300	820	II/28	> 80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	1080	II/28	> 80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6-rows	470	440	920	II/28	> 80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1180	II/28	> 80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	8-rows	320	580	1450	II/28	> 80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
ROLLSTAR potato version (4 stars / row) up to 80 cm row spacing	X-rows	C	C	C	C	> 80	C	C	✓	C	C	C	C	C	C	C	C	C	C
	2-rows	190	160	520	II/28	> 80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	3-rows	250	230	490	II/28	> 80	70	30/22	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	330	300	750	II/28	> 80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
		300	300	1010	II/28	> 80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
	6-rows	470	440	800	II/28	> 80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
		300	440	1060	II/28	> 80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
	8-rows	320	580	1450	II/28	> 80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
HILLSTAR up to 80 cm row spacing	12-rows	320	860	2000	II/28	> 80	70	140/103	-	●	●	●	●	-	-	-	✓	-	-
	X-rows	C	C	C	C	> 80	C	C	C	C	C	C	C	C	C	C	C	C	C
	2-rows	165	160	360	II/28	65-80	70	20/15	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	300	300	600	II/28	65-80	70	40/30	✓	●	●	●	●	-	✓	-	-	-	-
	4-rows	280	300	720	II/28	65-80	70	50/37	✓	●	●	●	●	-	-	✓	-	-	-
		440	440	850	II/28	65-80	70	60/44	✓	●	●	●	●	-	✓	-	-	-	-
	6-rows	300	440	980	II/28	65-80	70	60/44	✓	●	●	●	●	-	-	✓	-	-	-
		580	580	1040	II/28	65-80	70	80/59	✓	●	●	●	●	-	✓	-	-	-	-
	8-rows	320	580	1350	II/28	65-80	70	80/59	✓	●	●	●	●	-	-	✓	-	-	-
		480	860	1580	II/28	65-80	70	120/88	-	●	●	-	-	-	-	✓	-	✓	●
CHOPSTAR-HYBRID 1 plate 25-50 cm row spacing	12-rows	300	860	2100	II/28	65-80	70	140/103	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	65-80	C	C	C	C	C	C	C	C	C	C	C	C	C
	6-rows	300	300	660	II/28	25-50	45	60/44	✓	●	●	●	●	-	✓	-	-	-	-
	8-rows	300	380	990	II/28	25-50	45	70/51	✓	●	●	●	●	-	-	✓	-	-	-
	12-rows	305	560	1380	II/28	25-50	45	90/60	✓	●	●	●	●	-	-	✓	-	-	-
	15-rows	300	695	1780	II/28	25-50	45	100/99	-	●	●	-	-	-	-	✓	-	-	-
	18-rows	480	830	2120	III/36	25-50	45	130/96	-	●	●	-	-	-	-	✓	-	✓	●
		300	830	2310	II/28	25-50	45	130/96	-	●	●	-	-	-	-	-	✓	-	-
	24-rows	670	1100	2700	III/36	25-50	45	160/118	-	●	●	-	-	-	-	✓	-	✓	●
		420	1100	2910	III/36	25-50	45	160/118	-	●	●	-	-	-	-	-	✓	-	-
	X-rows	C	C	C	C	19-30	C	C	C	C	C	C	C	-	C	C	C	C	C

Conversion cm in inch = cm / 2,54 Conversion cm in feet = cm / 30,48

✓ = standard equipment

● = optionally available

V = version (selection)

C = customer adaption or request

- = not possible

	PROTECTIVE ELEMENTS					WORKING TOOLS													ACCESSORIES				
	Discs		Rotary hoe crop-protection-star	Sheets	Without	Tines	Elements	Cutting plate	Angle knives	Cutting discs	Hoeing stars	Heaping sweeps	Heaping elements	Heaping discs	Weeder tines behind the element	Guided hill weeder	Finger hoe	Rotation weeder element	Section Control Hydr. folding system	Seeder P-BOX-STI JUMBO-SEED	Warning signs + LED lights to the rear	Warning signs + LED lights to the front and rear	Warning signs for front units with indicator to the front
	-	●	-	●	✓	4	3	-	-	-	16	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	8	5	-	-	-	32	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	8	5	-	-	-	32	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	12	7	-	-	-	48	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	12	7	-	-	-	48	-	-	-	-	●	●	●	●	●	●	●	-
	-	●	-	●	✓	16	9	-	-	-	64	-	-	-	-	●	●	●	●	●	●	●	-
	-	C	-	C	C	C	C	-	-	-	C	-	-	-	-	C	C	C	C	C	C	C	C
	-	-	-	●	✓	3	3	-	-	-	8	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	4	4	-	-	-	12	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	5	5	-	-	-	16	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	5	5	-	-	-	16	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	7	7	-	-	-	24	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	7	7	-	-	-	24	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	9	9	-	-	-	32	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	●	✓	13	13	-	-	-	48	-	-	-	-	●	●	●	●	●	●	●	-
	-	-	-	C	C	C	C	-	-	-	-	-	-	-	-	C	C	C	C	C	C	C	C
	-	-	-	-	✓	3	3	-	-	-	-	-	-	4	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	5	5	-	-	-	-	-	-	8	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	5	5	-	-	-	-	-	-	8	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	7	7	-	-	-	-	-	-	12	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	7	7	-	-	-	-	-	-	12	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	9	9	-	-	-	-	-	-	16	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	9	9	-	-	-	-	-	-	16	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	13	13	-	-	-	-	-	-	24	-	●	-	-	●	●	●	●	-
	-	-	-	-	✓	13	13	-	-	-	-	-	-	24	-	●	-	-	●	●	●	●	-
	-	-	-	-	C	C	C	-	-	-	-	-	-	-	-	C	-	-	-	C	C	C	C
	●	-	-	●	✓	-	7	7	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	●	-	-	●	✓	-	9	9	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	●	-	-	●	✓	-	13	13	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	●	-	-	●	✓	-	16	16	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	●	-	-	●	✓	-	19	19	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	●	-	-	●	✓	-	19	19	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	●	-	-	●	✓	-	25	25	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	●	-	-	●	✓	-	25	25	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-
	C	-	-	C	C	-	C	C	-	-	-	-	-	-	-	-	C	C	C	C	C	C	-

Please clarify directly with an Einböck consultant whether additional options can be combined with each other or whether special parts may be required for options to be implemented (e.g. deviation from row spacing).



CAMERA STEERING SYSTEM ROW-GUARD

Type/ Working width cm	Info	Hoe kg / lbs	Weight approx. kg / lbs
ROW-GUARD 500	for frame up to 6.99 m / 22.90 ft	≤ 2500 / 5511	390 / 859
ROW-GUARD 500 SR	for frame up to 12.2 m / 40.00 ft	≤ 3900 / 8598	530 / 1168
ROW-GUARD 500 SRHD	for frame up to 12.2 m / 40.00 ft	> 4000 / 8818	960 / 2116

Technical changes and mistakes are subject to change without prior notice!

In order to introduce the benefits of our continuous product development, we reserve the right to make technical changes without prior notice. Printing and typesetting errors or changes of any kind do not entitle the customer to any claims. Individual equipment specifications, which are illustrated or described here, are only available as options.

In case of contradictions between individual documents regarding the scope of supply, the information in our current price list shall apply.

All pictures are symbol pictures and may contain options which are available for an additional charge. For further information please contact our sales team.

Photos & Graphics: © Einböck GmbH; Photos & Graphics free, without licence, but can be used only unchanged | Text & Content: © Einböck GmbH; can be used unchanged if source is cited | Version 1: 04/2021